

- > Color MFP
- > Up to 42 PPM
- > Small/Med. Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP



C:studio 287csl/347csl/407cs

Affordable, high-impact color.

You need black and white, but you'd like to add color. Now they're both available in a compact size at a sensible price, thanks to the new e-STUDIO407cs series from Toshiba. Copy, print, scan and fax with the MFP that does it all, for less.

Your MFP has arrived.

Small and medium size businesses. from healthcare to education to finance, can now take advantage of everything Toshiba MFPs have to offer, in a surprisingly small package. The new e-STUDIO407cs series prints black and white or color at speeds of up to 42 PPM for letter size paper and 34 PPM for legal size. It incorporates leading LED technology that reduces the overall size and simplifies the design. An e-BRIDGE Universal Print Driver, the single driver for all Toshiba e-BRIDGE series models, includes plugins for the simple addition of a variety of productivity enhancing options.

Compact, powerful, and groundbreaking.

A long list of impressive features and benefits are available on the e-STUDIO407cs series. The e-BRIDGE technology provides consistency across our family of MFPs. After you've learned one, you can operate many. They all use the same operability, user interface, open platform connectors, cloud and mobile printing and scanning, and management utilities.

The e-STUDIO407cs series has a small footprint so it's lightweight and it also operates quietly. Maintenance is simpler than ever because of replacement units that can be easily installed by anyone. The color output is incredible, too, with enhanced image quality and vivid, glossy colors.

TOSHIBA

STUDIO407cs

UTTER

Leading innovation in high security.

Data has never been more secure. The e-STUDIO407cs series incorporates proprietary Toshiba technology in a number of ways to provide a level of data protection for IT equipment that sets a new standard.

Security matters.

Toshiba's e-STUDIO407cs series addresses the most stringent security requirements of the IEEE2600 standards for multifunction products. Our proprietary 320GB Self-Encrypting-Drive (SED) features Automatic Data Invalidation, virtually eliminating the possibility that data can be retrieved from the drive should it be removed and placed into another device. This Toshiba design utilizes the 256 Advanced Encryption Standard (AES) and is FIPS 140-2 Validated, while the data overwrite feature meets Department of Defense requirements. Even data being sent to or from the e-STUDIO407cs series can be encrypted using the optional IPsec Enabler.

Keeping your data safe.

Other MFP features help make sure you only share the information you want to share. The Secure PDF feature lets users scan and email documents at the MFP using a password so only those recipients who know the password can access the document.

Whatever your security concerns may be, with the Toshiba e-STUDIO407cs series and the protection it affords, you can rest assured your documents are safe.







Not only can you perform multiple functions with ease, everything you do is protected with advanced security measures.



Take advantage of scalable configurations. You can create a convenient desktop version. Or, add paper capacity and functionality as needed.

> Self Encrypting Drive

- > IPsec Enabler (optional)
- > IP Filtering
- > Network Port Control
- > Secure PDF
- > Private Print



Technologically advanced, environmentally sound.



TOSHIBA Leading Innovation >>>

Toshiba began developing innovative ways to reduce environmental impact long before it became the popular thing to do. In addition to a smaller footprint with regard to size, the e-STUDIO407cs series also has a smaller ecological footprint.

Protecting precious resources in more ways.

While we're busy working to help save the environment, we're also helping you save money. The e-STUDIO407cs series uses a mono component development method that eliminates waste material. An enhanced Sleep Mode has a 1.5 W power consumption to further reduce energy usage. Other ways in which Toshiba puts environmental responsibility into action include a recycling program, reduction of CO2 emissions, and the recycling of plastics. Reduction and elimination of hazardous materials such as lead and mercury enable the series to comply with environmental standards around the world. In addition, the series is Energy Star Tier 2 compliant.

Green Matters.

From our zero-waste-to-landfill toner recycling to greener manufacturing, Toshiba is a recognized environmental leader. We're investing in programs that help both our business and yours reduce, reuse and recycle.

Encompass Assessment and Green Report.

Toshiba's Encompass Assessment examines all output devices and determines your company's current environmental impact.

The data is delivered in a Green Report where we highlight simple solutions to support your environmental initiatives.



The e-STUDIO407cs series has unique stacking drawers and spacers that allow you to configure your device to fit your specific needs. Put together a configuration that's just right for you by choosing from a countertop base model or up to three additional drawers and/or spacers along with a space-saving inner finisher*.



Exceptional features, starting with e-BRIDGE.

The outstanding performance of the e-STUDIO407cs series is due, in large part, to advanced e-BRIDGE technology. This Toshiba e-STUDIO series is available for small and medium size businesses looking for outstanding color and powerful features in a letter size MFP. The list of features is impressive, including Universal Print Drivers with plug-ins, web browsing and printing, open platform connectors and mobile printing. Additional features and benefits include:



Compact, lightweight, and packs a punch

This powerful, compact letter and legal size device saves space and money, offering one of the smallest footprints among comparable MFPs.



LED print head

An innovative LED light source for printing results in low noise, easy maintenance and a smaller, more compact size.



Impressive image quality

Get attention-grabbing gloss output using a greater range of colors. Choose from a variety of media including 17lb bond to 138lb index and 3"x 5" index cards to 8.5" x 52" banners, all with up to 600 x 1200 dpi output.



High performance print engine

A technologically advanced, high performance print engine allows for a faster warm-up and First Copy Out Time. Not to mention an overall energy reduction to help the environment and your budget.



Easy to use

Now it's easier than ever to operate an MFP. Thanks, in part, to a 9-inch display consistent with other Toshiba devices, hard keys or buttons used for main functions, and an e-BRIDGE Open Platform for flexible integration.



Easy to maintain

Replacing supplies and performing routine maintenance are simple and can be performed by virtually anyone, reducing the need for a service call.

Plenty of options

Choose from a variety of options to take greater advantage of the e-STUDIO407cs series. There's a space-saving Inner Finisher, 2,000-Sheet LCF up to 4-drawer configuration. Also, Job Point for cluster printing with up to 10 e-STUDIO models and Re-Rite for one-touch automatic OCR as well as a Fax Unit, Wireless LAN Module, and IPsec Enabler.





Managed Print Services

Look to our highly experienced Managed Print Experts to help you cut costs, streamline operations, control your output environment, secure documents, and reduce your environmental impact.

And that's not all

The list of outstanding features goes on and on. In fact, it goes something like this: Job Skip allows you to skip to the next job if one job runs out of paper or toner. Omit Blank Page removes all blank pages from all jobs. Outside Erase lets you copy or scan books and 3D objects with the RADF open. Envelope Printing can be done straight from the bypass. The One Touch Templates function automates complex or frequently repeated jobs. Standard Tandem Printing completes large jobs faster by dividing the work between two printers. And, e-Filing lets you print, edit and manage stored documents.

C-STUDIO[®] 287csL/347csL/407cs





- > Color MFP
- > Up to 42 PPM
- > Small/Med. Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP

Specifications

| Copying TypeLED Head PrintingCopy/Print Resolution600/600 x 600/1200 dpiCopy/Print Speed30/30, 35/37, 42/42, PPM Color/B&WWarm-Up TimeApprox. 60 SecondsFirst Copy Out Time13 SecondsMultiple CopyingUp to 999 CopiesAcceptable Paper SizeCassette: ST-R to LG (17lb Bond - 120lb Index)and WeightBypass: 3" x 5" to LG,Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GBHD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-SheetPaper SupplyUp to 2,630-Sheet Input CapacityStandard 1 x 530-Sheet Cassettes100-Sheet ExpassOptional 3 x 530-Sheet LCFOptional 3 x 530-Sheet CassetteDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H)407cs: Approx. 112.43lbCMYY Toner YieldCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | Copying Process | Direct Electrostatic Photographic Transfer System with Internal Transfer Belt |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|----------------------------------------------------------------------------------|
| Copy/Print Resolution600/600 x 600/1200 dpiCopy/Print Speed30/30, 35/37, 42/42, PPM Color/B&WWarm-Up TimeApprox. 60 SecondsFirst Copy Out Time13 SecondsMultiple CopyingUp to 999 CopiesAcceptable Paper SizeCassette: ST-R to LG (17lb Bond - 120lb Index)and WeightBypass: 3" x 5" to LG, Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Cassettes 100-Sheet ExpassDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) | Copying Type | , |
| Copy/Print Speed30/30, 35/37, 42/42, PPM Color/B&WWarm-Up TimeApprox. 60 SecondsFirst Copy Out Time13 SecondsMultiple CopyingUp to 999 CopiesAcceptable Paper SizeCassette: ST-R to LG (17lb Bond - 120lb Index)and WeightBypass: 3" x 5" to LG,memory (Max)Main Memory: 2GBPocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet *Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | 1,5 0,51 | 8 |
| Warm-Up TimeApprox. 60 SecondsFirst Copy Out Time13 SecondsMultiple CopyingUp to 999 CopiesAcceptable Paper SizeCassette: ST-R to LG (17lb Bond - 120lb Index)and WeightBypass: 3" x 5" to LG,Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GBHD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input CapacityStandard 1 x 530-Sheet Cassettes100-Sheet BypassOptional 3 x 530-Sheet CassetteOptional 3 x 530-Sheet CassetteOptional 3 x 530-Sheet LCFDuplexDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H)407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | | |
| First Copy Out Time13 SecondsMultiple CopyingUp to 999 CopiesAcceptable Paper SizeCassette: ST-R to LG (17lb Bond - 120lb Index)and WeightBypass: 3" x 5" to LG, Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 112.43lbWeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15K Power SupplyValueL20 V, 8 Amps | | |
| Multiple CopyingUp to 999 CopiesAcceptable Paper Size and WeightCassette: ST-R to LG (17lb Bond - 120lb Index) Bypass: 3" x 5" to LG, Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%) BypassDypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 112.43lbWeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15K Power SupplyPower Supply120 V, 8 Amps | | |
| Acceptable Paper Size and WeightCassette: ST-R to LG (17lb Bond - 120lb Index) Bypass: 3" x 5" to LG, Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%) 100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 112.43lbWeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15K Power Supply | | |
| and WeightBypass: 3" x 5" to LG, Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet BypassDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | | |
| Banner 8.5" x 52" (17lb Bond - 138lb Index)Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet BypassOptional 3 x 530-Sheet Cassette Optional 3 x 530-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index) 407cs: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | | · · · · · · · · · · · · · · · · · · · |
| Memory (Max)Main Memory: 2GB HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet BypassDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | | 51 |
| HD: 320GB FIPS 140-2 Validated SEDDocument Feeder100-SheetReduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input CapacityStandard 1 x 530-Sheet Cassettes100-Sheet BypassOptional 3 x 530-Sheet CassetteOptional 3 x 530-Sheet CassetteDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | Memory (Max) | |
| Reduction/Enlargement25% to 400% (RADF: 25% to 200%)Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet Bypass Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index) 407cs: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 112.43lbWeightApprox. 112.43lb CMYK Toner YieldPower Supply120 V, 8 Amps | | HD: 320GB FIPS 140-2 Validated SED |
| Bypass100-Sheet "Smart" Bypass (17lb Bond - 138lb Index)Control PanelColor 9" LCD Touch PanelPaper SupplyUp to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet BypassDuplexDytional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index) 407cs: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lb CMYK Toner YieldPower Supply120 V, 8 Amps | Document Feeder | 100-Sheet |
| Control Panel Color 9" LCD Touch Panel Paper Supply Up to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet Bypass Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCF Duplex Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | Reduction/Enlargement | 25% to 400% (RADF: 25% to 200%) |
| Paper Supply Up to 2,630-Sheet Input Capacity Standard 1 x 530-Sheet Cassettes 100-Sheet Bypass Optional 3 x 530-Sheet Cassette Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCF Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | Bypass | 100-Sheet "Smart" Bypass (17lb Bond - 138lb Index) |
| Standard 1 x 530-Sheet Cassettes 100-Sheet Bypass Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCF Duplex Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | Control Panel | Color 9" LCD Touch Panel |
| 100-Sheet BypassOptional 3 x 530-Sheet CassetteOptional 2,000-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index)Dimensions287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H)407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | Paper Supply | Up to 2,630-Sheet Input Capacity |
| Optional 3 x 530-Sheet Cassette Optional 2,000-Sheet LCFDuplexStd. Automatic Duplex Unit (17lb Bond - 120lb Index) 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H)WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15K Power Supply120 V, 8 Amps | | Standard 1 x 530-Sheet Cassettes |
| Optional 2,000-Sheet LCF Duplex Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | | 100-Sheet Bypass |
| Duplex Std. Automatic Duplex Unit (17lb Bond - 120lb Index) Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | | Optional 3 x 530-Sheet Cassette |
| Dimensions 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | | Optional 2,000-Sheet LCF |
| 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) Weight Approx. 112.43lb CMYK Toner Yield CMY: 11.5K, BK: 15K Power Supply 120 V, 8 Amps | Duplex | Std. Automatic Duplex Unit (17lb Bond - 120lb Index) |
| WeightApprox. 112.43lbCMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | Dimensions | 287csL/347csL: Approx. 20.6" x 23.8" x 26.4" (W x D x H) |
| CMYK Toner YieldCMY: 11.5K, BK: 15KPower Supply120 V, 8 Amps | | 407cs: Approx. 20.6" x 23.8" x 31.9" (W x D x H) |
| Power Supply 120 V, 8 Amps | Weight | Approx. 112.43lb |
| | CMYK Toner Yield | CMY: 11.5K, BK: 15K |
| Dower Concurrentian Maximum 1 E IAN | Power Supply | 120 V, 8 Amps |
| | Power Consumption | Maximum 1.5 kW |
| Max Duty Cycle 85K/100K/125K Copies | Max Duty Cycle | 85K/100K/125K Copies |

e-BRIDGE Print Specifications

| PDL Support Operating Systems | PCL6, PostScript 3, XPS Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, |
|----------------------------------|------------------------------------------------------------------------------|
| | NetWare 6.5, Citrix, Macintosh 10.4-10.9, |
| | Solaris v10, 11, HP-UX V11.iv3, AIX 7.x, Linux, SCO |
| Protocol Support | Windows Printing (SMB1.0/2.0), LPR/LPD, IPP (Ver.1.1) |
| | w/Authentication, NetWare P-SERVER w/NDS, Binary, |
| | Novell NDPS Gateway, or LPD w/iPrint, Apple Talk PAP or |
| | EtherTalk, Port 9100 (bi-directional), WS Print, FTP |
| Drivers | Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, |
| | Macintosh OS 10.4-10.9 |
| Connectivity | 10/100/1000BaseTX Ethernet, |
| | 802.11b/g/n, Wireless LAN, USB |
| Wireless Device | AirPrint, e-BRIDGE Print & Capture Application on iOS and |
| | Android (Available via Apple App Store or Google Play) |
| Device Management | Top Access, eFMS 6.0 (e-BRIDGE Fleet |
| 0 | Management Software) |
| Certification | Windows 7, 8, 8.1, 2008R2, 2012, 2012 R2, |
| | WHQL, Novell, Citrix |
| | , , |

Scan Specifications

| Scan Resolution | 100 dpi, 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi |
|-----------------|------------------------------------------------------|
| Scan Speed | 40 SPM Color/40 SPM B&W (@ 300 dpi) |
| File Format | TIFF, PDF, Secure PDF, JPEG, XPS |

Facsimile Specifications

Compatibility Super G3 MH/MR/MMR/JBIG Data Compression Transmission Speed Approx. 3 Seconds Per Page Fax Modem Speed 33.6 Kbps Maximum 40 SPM

Scan Speed



E-Filing Specifications

| Operation Method | Color Touch Screen Control Panel or Clie | nt PC | |
|----------------------------------------------------------|-----------------------------------------------------------------|-----------|--|
| Number of Boxes | 1 Public Box, 200 Private User Boxes | | |
| Capacity of Boxes | 100 Folders Per Box, 400 Documents Pe 200 Pages Per Document | r Folder, | |
| Security | 5 | | |
| Data Encryption & Disk Overwrite | 256 Bit AES (SED Hard Drive) | | |
| Authentication | LDAP, SMTP, Windows Server Domain, L | ocal | |
| Accessories (Opti | ons) | | |
| Additional Paper Op | tions, Spacers, Caster Base | | |
| Spacer: (For Adjusting Machine Height Replacing a Stand) | | | |
| Caster Base: (Caster Base for PFU, LCF or Spacer) GR | | | |

Cassettes: 530-Sheet Pedestal, 8.5SQ to 14LG MY1045 Large Capacity Feeder (LCF): 2,000-Sheet Drawer, LT, KD1040 13LG, 13.5LG, 14LG, A4 **Finishing Options** Inner Finisher (e-STUDIO407cs Only): MJ1038 1 Tray: 500 Sheets Damper Kit (Required for MJ1038) KK1002 MJ1039 Offline Stapler **Connectivity/Security Options** GD1340 Fax Board Wireless Module GN1060 Wireless Antenna GN3010 Meta Scan Enabler for e-CONNECT GS1010 **IPsec Enabler** GP1080 Advanced Scanning (Re-Rite) GB1280V8 SharePoint Connector GB1440 Exchange Connector GB1450 Google Docs Connector GB1540



| Corporate Office | 9740 Irvine Blvd., Irvine, CA 92618-1631 Tel: 949-462-6000 |
|------------------|---------------------------------------------------------------------------|
| East Coast | 959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-316-2700 |
| Midwest | 8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000 |
| South | 2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385 |
| West Coast | 9740 Irvine Blvd., Irvine, CA 92618 Tel: 949-462-6000 |
| Web Site | www.business.toshiba.com |

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support vary by client/network operating system.

© 2014 Toshiba America Business Solutions, Inc. Electronic Imaging Division Inv. Code: 22266 407cs Short Series Brochure 3K PG 7/14