

## **e-STUDIO™ 2520AC**

- Up to 25 PPM
- Compact Design
- Feature Rich
- Advanced Security Options
- Environmentally Friendly



## MAIN SPECIFICATIONS

<b>Copy System</b>	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
<b>Display</b>	10.1" Color WSVGA Touch Screen Tilting Display
<b>Copy Speed</b>	25 PPM (LT)
<b>First Copy Out</b>	Color: Less Than 9.5 Seconds Monochrome: Less Than 7.1 Seconds
<b>Warm-Up Time</b>	From powering on: Approx. 21 Seconds From Sleep & Low Power: Less Than 15 Seconds
<b>Copy Resolution</b>	600 x 600 dpi
<b>Stack Feed Bypass</b>	3.9" x 5.8" to 11" x 17", Envelope
<b>Multiple Copying</b>	Up to 999 Copies
<b>Paper Capacity</b>	Standard 350 Sheets/Max. 2,900 Sheets
<b>Original Feed</b>	100-Sheet RADF
<b>Scan Speed &amp; Weights</b>	RADF Scan: 50 IPM (Monochrome or Color), Simplex: 9.3-41.8lb Bond Duplex: 13.3-41.8lb Bond
<b>Max. Original Size</b>	LD/A3
<b>Paper Feed Sizes</b>	Drawer 1: 250 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. PFU: 550 Sheets-ST-R to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP-ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 250 Sheets-16lb Bond-90lb Index Stack Feed Bypass: 100 Sheets-16lb Bond-90lb Index Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-90lb Index Opt. 550 Sheets Drawer for PFP-16lb Bond-90lb Index Opt. Envelope Cassette for PFP-16lb Bond-90lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-90lb Index Standard Automatic Duplex Unit (16lb Bond-90lb Index)
<b>Paper Weights</b>	25% to 400% Max. 84K Month (Color: 100%) Max. 84K Month (Monochrome: 100%) Approx. 125lb
<b>Duplex</b>	26" (W) x 23" (D) x 31" (H)
<b>Reproduction Ratio</b>	CMY: 38K, K: 39.8K @ 5%
<b>Max Duty Cycle</b>	120 Volts, 50/60 Hz, 12 Amps
<b>Weight</b>	Maximum 1.5kW (120V)
<b>Approx. Dimensions</b>	NEMA 5-15
<b>CMYK Toner Yield</b>	4GB
<b>Power Source</b>	128GB Solid State Drive (SSD)
<b>Power Consumption</b>	
<b>Plug Type</b>	
<b>Memory</b>	
<b>Hard Disk Drive</b>	

## e-BRIDGE NEXT PRINT SPECIFICATIONS

<b>PDL</b>	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
<b>Print Resolution</b>	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
<b>Operating Systems</b>	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
<b>Network Protocols</b>	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
<b>Printing Protocols</b>	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
<b>Print Drivers</b>	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
<b>Interface</b>	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
<b>Wireless Device</b>	TopAccess
<b>Device Management</b>	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
<b>Account Control</b>	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist
<b>Accessibility Features</b>	



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

## Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication \*Conformance with HCD-PPv1.0 in High Security Mode ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

## Environmental Standards Certifications

## SCAN SPECIFICATIONS

<b>Scan Speed</b>	RADF Scan: Up to 73 IPM (Monochrome or Color)
<b>Scan Modes</b>	Standard: Full Color, Auto Color, Monochrome, Grayscale
<b>OCR</b>	DOC/XLS/PPT/PDF
<b>Scan Resolution</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>File Formats</b>	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX, Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
<b>Image Compression</b>	Color/Grayscale: JPEG (High, Middle, Low)

## FACSIMILE SPECIFICATIONS

<b>Compatibility</b>	Super G3
<b>Data Compression</b>	MH/MR/MMR/JBIG
<b>Transmission Speed</b>	Approx. 3 Seconds Per Page
<b>Fax Modem Speed</b>	Up to 33.6 Kbps
<b>Memory Transmission</b>	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
<b>Scan Speed</b>	0.7 Seconds Per Page, Maximum 73 IPM

## e-FILING SPECIFICATIONS

<b>Operation Method</b>	Color Touch Screen Control Panel or Client PC
<b>Number of Boxes</b>	1 Public Box, 200 Private User Boxes
<b>Capacity of Boxes</b>	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

## ACCESSORIES (OPTIONS)

<b>Platen &amp; Document Feeder Options</b>			
RADF	MR3033	e-BRIDGE Replicator	GB1550NODE
Platen Cover	KA5005PC	e-BRIDGE Job Point	GB1560NODE
<b>Additional Paper Options</b>		e-BRIDGE Job Separator	GB1590NODE
Paper Feed Unit	MY1051	e-BRIDGE Job Build	GB1610NODE
Paper Feed Pedestal	KD1072	e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Drawer Module	MY1052	e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
Envelope Cassette Option	MY1053	e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
Large Capacity Feeder	KD1073LT	e-BRIDGE Plus for Gmail	GB2380NODE
<b>Finishing Options</b>		e-BRIDGE Plus for Google Workspace	GB2390NODE
50-Sheet Inner Finisher	MJ1048	Hardcopy Security Printing	GP1190NODE
65-Sheet Saddle-Stitch Finisher	MJ1114	Security SSD (512GB)	GE1280
Hole Punch for MJ1048	MJ6011	FIPS HDD (320GB)	GE1260
Hole Punch for MJ1113/MJ1114	MJ6107	e-BRIDGE Plus Voice Guidance	GB2540NODE
Bridge Kit	KN5005	e-BRIDGE Global Print	GB2550NODE
Job Separator	MJ5014	<b>Miscellaneous Options</b>	
<b>Connectivity/Security Options</b>		Card Reader Holder	GR1320
FAX Unit/2 <sup>nd</sup> Line for FAX Unit	GD1370N	Accessory Tray	GR1330
Wireless LAN/Bluetooth	GN4030A3	Panel 10-Key Option	GR1340
Fax Over IP License Key	GS1100NODE	Stand	STAND5015
Bluetooth Keyboard	GR9001	Work Tray	KK5005
2 <sup>nd</sup> NIC Holder	GR1430	Manual Pocket	KK5008
USB Hub	GR1420	Harness for Coin Controller	GQ1280
Meta Scan Enabler	GS1010NODE	Accessible Arm	KK2560
External Interface Enabler	GS1020		
IPSec Enabler	GP1080NODE		
Unicode Font Enabler	GS1007NODE		
Multi-Station Print Enabler			
Per Seat License	GS1090NODE		

## Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## Website

www.business.toshiba.com